



# WiFi Version Microinverter Installation Guide

Zhejiang Hyxi Technology Co., Ltd.

Quality

Innovation

Efficiency

Win-win

# Contents

1

**Preparation**


2

Physical Installation

3

APP Configuration

# Preparation-1 Network




**Before installation, installer should survey the site at least once.**

1. Please communicate with the end user and place the router on the **top floor**.
2. If the router really can not be placed on the top floor, it' s better to adjust the position of the router as close to the roof as possible in the first floor. And then place a **WiFi repeater(signal extender)** in the top floor.

# Preparation-1 Network

Stand in the installation position of the microinverter on roof and use professional signal detection tools to check the signal values of router or WiFi repeater.



**It is recommended that the value of network within 0~-50 dBm**

**Need to adjust the network.**

After installation, when system is running ,due to the interference of cables and metal brackets, the final signal (microinverter-router ) displayed in Hyxipower APP will be about **-60dBm**.

## Alternative solution :

1. APP(WiFi Analyzer).

Notice :the accuracy is weaker than professional signal detection tools.

2. WiFi page of the phone.


1.Google Play Store  
Or Apple Store  
Search **"WiFi Analyzer"**





WiFi Analyzer  
(open-source)



2. Signal value icon.



# Preparation-2 Materials



**A:** AC Branch Connector  
**B:** Antenna  
**C:** DC terminal  
**Note:** Appearances may vary depending on the model.

**Notice!! Installer have to buy these accessories locally:**

NO.	Product Name	Model	Description	Remark
1	<b>Screws</b>	M8*25	Used to fix microinverter	Buy Locally
2	<b>PV cable</b>		PV panel to Microinverters	Buy Locally or from Hyxipower
3	<b>Ground wire</b>	4~10mm <sup>2</sup>	For equipment grounding	Buy Locally

# Preparation-2 Materials by Hyxipower




## Product material list

No.	Product Name	Picture	Model	Description
1	DC Extension Cable		DC-EC-1m	1 DC male+1 cable (1m)+1 DC female Used to extend the connection distance between micro inverters and photovoltaic modules
2	T-junction Bus End Plug		T-JB-EP	Used to protect unused bus connection ports on AC bus connectors at the end of AC branches
3	T-junction Branch Port Protection Cover		T-JB-PPC	Used to protect unused branch connection ports on AC bus connectors
4	T-junction Removal Tool		T-JB-RET	Used to remove the upper cover of the AC bus connector for loading, unloading, or replacing the AC bus cable
5	T-junction Bus Connector		T-JB-Con	One T-junction Bus Connector(without cable) The AC bus connector is used to connect the AC output of the micro inverter to the AC bus
6	DC Connector Removal Tool		DC-Con-RET	Used to disassemble the connection between the photovoltaic module and the input of the micro inverter
7	T-junction connecting wire		TJ-Cable-20T-19L-10AWG-1.6m; TJ-Cable-13T-12L-10AWG-3m; TJ-Cable-7T-6L-10AWG-5.7m	20 T-junction, 19 cables (1.6m/3m/5.7m long, <b>10AWG</b> , brown blue insulation layer), <b>32A</b> max for the use. It can be used to connect the micro inverter to the distribution box for AC side convergence.

# Preparation-3 Junction Connecting Wire

## Single-row vertical installation

1-in-1 <1.6m




TJ-Cable-20T-19L-10AWG-1.6m-NA

2-in-1 <3m



TJ-Cable-13T-12L-10AWG-3m-NA


4-in-1 <3m



TJ-Cable-7T-6L-10AWG-5.7m-NA

## Double-row vertical installation

1-in-1 <1.6m



TJ-Cable-20T-19L-10AWG-1.6m-NA

2-in-1 <1.6m



TJ-Cable-20T-19L-10AWG-1.6m-NA

4-in-1 <3m



TJ-Cable-13T-12L-10AWG-3m-NA

■ Microinverter   ■ photovoltaic panel   — AC wire

# Preparation-3 Junction Connecting Wire

## Single-row horizontal installation

1-in-1 <3m



2-in-1 <5.7m



4-in-1 <11m



■ Microinverter

■ photovoltaic panel

— AC wire

## Double-row horizontal installation


1-in-1 <3m



2-in-1 <3m



4-in-1 <5.7m





# Preparation-4 Tools

Please prepare professional electrician tools in advance



Wire stripper



Wire nippers



Screwdriver




Multimeter



Marker



Cable tie



Dust mask



Goggles



Safety shoes



Safety gloves



Tape measure



Hexagon wrench

# Contents

1

Preparation


2

**Physical Installation**


3

APP Configuration


# Physical Installation-1 T-Junction Bus End Plug




Use the T-junction removal tool to remove the lower cover.



Loosen the inner screw, unscrew the nut, and remove the cable.




Install a T-junction bus end plug at the end of the T-junction.




Insert the lower T-junction cover back into place and make sure it is secure.

**The meaning of this step is to install the two end plugs of the micro inverter grid connection wire.**


# Physical Installation-2 T-Junction Bus Connector




Prepare the AC cable by stripping the ends.



Insert the AC cable into the T-junction connector at the correct hole position.




Tighten the screws, and then the nuts.



Insert the lower T-junction cover back into place, making sure it is secure.

**The meaning of this step is to install the connector in the micro inverter grid connection wire.**


# Physical Installation-3 Draw Installation Map



Tear off the serial number label of microinverter then paste on the corresponding position. Then it can quickly find the corresponding photovoltaic panel and inverter, and can be easily used to make intelligent Layout of photovoltaic panels.

**Note: Please tear off the label paper before fixing the microinverter to avoid problems that are difficult to tear off after fixing the device.**


# Physical Installation-4 Microinverter Installation



**Step 1:** Mark the installation position of the microinverter on the bracket according to the layout of the photovoltaic modules.


**Step 2:** Fix the microinverter on the bracket with M8\*25mm screw, then lock the screw.

# Physical Installation-5 Connect Microinverter



Insert the output AC feeder connector of the microinverter into the T-junction bus connector until hearing a "click" sound. Ensure that the installation is tight.

# Physical Installation-6 Connect PV Module



**Step 1:** Install the PV module above the microinverter.

**Step 2:** Connect the DC output cable of the PV module with the input side of the microinverter.



# Physical installation-7 Power on



Light	Status	Description
Green	Fast flashes (1s gap)	Normal
	Slow Flashes (3s gap)	Communication error
	Slow Flashes (3s gap)	PV input error
Light	Status	Description
Red	Light on	Ground error
	Fast flashes(1s gap)	Error
	Fast flashes(2s gap)	AC error

**Step 1:** Close the main grid circuit breaker.

**Step 2:** Close the AC circuit breaker of each microinverter branch.

**Step 3:** The green lights blinks briefly indicates startup success.

# Contents



Preparation



Physical Installation



**APP Configuration**

## Download and Registration

1. Download HYXipower APP.
  2. Register the account of the person in charge of the organization.
- 

## Near-end Configuration

### **Register the WiFi microinverter to the cloud server through Configuration.**

All HYXiPOWER's equipment is managed by the cloud platform. After the equipment is registered to the cloud server, it can be managed uniformly through the cloud platform.

---

## Crear Plant for Users

### **Create a plant for users**

Manage the equipment through the Plant and check the equipment status, system power generation and usage, etc.

---

## Check Signal Strength

### **Check the signal strength of the microinverter after the configuration.**

Ensure that microinverter, software and mobile data transmission are normal.

---

# APP Configuration-1 Download and Registration




The entire installation process requires 2 email accounts: Organization & Owner.

**Step1:**Organization account :**Register Now.**


## App Store

Search "HYXipower"



## Google Play Store

Search "HYXipower"



More v

HYXiPOWER

Email/Phone No.

Password

Forgot Password? **Register Now**

I agree to the [Terms of Use](#) and I have read the [Privacy Policy](#)

**Log In**

Experience

**Step2 : Select Your Server, Register as Organization .**

Select Role

Please select the relevant server for your area

Select Your Server European Server >

If Your Role Is An Installer Or A Distributor, Please Register For The Following Role.

**Register as Organization** >  
Installer or Distributor

Register as Owner

Register as Owner >  
Plant Owner

If You Have Only Installed A Balcony Photovoltaic System, Please Register The Following Roles.

Registered Balcony System Homeowner >  
Balcony System Owner

Register as Organization

Note: If your organization or company has registered for an organization account in this system, you do not need to register again. Please contact your administrator to add you to the member list

Organization/ Company Name Please Enter

Registration Method

Please Enter @hotmail.com v

Please Enter **Send**

Complete Info

Password Please Enter

Confirm Password Please Enter





**Register**

I agree to the [Terms of Use](#) and I have read the [Privacy Policy](#)

# APP Configuration-1 Download and Registration



**Step3:** Log in the account,select **service-Member Management**, then select **+** to add the member. It' s recommand to select "administrator" .



## Download and Registration

1. **Download HYXipower APP.**
  2. **Register the account of the person in charge of the organization.**
- 

## Near-end Configuration

### **Register the WiFi microinverter to the cloud server through Configuration.**

All HYXiPOWER's equipment is managed by the cloud platform. After the equipment is registered to the cloud server, it can be managed uniformly through the cloud platform.

---

## Crear Plant for Users

### **Create a plant for users**

Manage the equipment through the Plant and check the equipment status, system power generation and usage, etc.

---

## Check Signal Strength

### **Check the signal strength of the microinverter after the configuration.**


Ensure that microinverter, software and mobile data transmission are normal.

---

# APP Configuration-Near-end Configuration





**Step 1:** Open the APP , if prompted to update the version, **update** it before configuration. Then select **More, Select Your Server-European Server(Europe, Africa, Asia (except China), Brazil, Argentina).** Then **Near-end Commissioning. Download**, will take about 1 minute .The Device Firmware Upgrade Package will stored in the phone.



# APP Configuration-Near-end Configuration

Step 2: **Scan** the Barcode of the Microinverter,  
**Join** the MI-XXXXXXXXXXXXX.

At the same time,  
another method is **Manually Connect**.





# APP Configuration-Near-end Configuration



## IOS operating system:

In phone's WIFI page, find: MI-XXXXXXXXXXXX; Connect it, WIFIPassword is **12345678** or **hyxi0607**; Connect successfully. **Return** to APP page. Then **Next**.

### APP Page





Keep the APP running and **manually** go to the WiFi page.

Input the WiFi password.

Then back to APP.

### Phone WiFi Page



### APP Page



# APP Configuration-Near-end Configuration




**Android operating system :**


**Switch Wi-Fi.** In phone's WIFI page, find: MI-XXXXXXXXXXXX; Connect it.

WIFI Password is **12345678** or **hyxi0607**; Connect successfully. **Return** to APP page. Then **Next**.

## APP Page




## Phone WIFI Page



Input the WiFi password.

Then back to APP.


## APP Page




# APP Configuration-Quick Settings




**Step 3:** Select **Installer**, enter the initial device access password: **hyxi0607**, **Log In** and modify the password, then Next. (Record the new password).



**Step 4:** **Quick settings**, Confirm the SN of microinverter.




**Step 5:** **Time Zone**, and corresponding **Grid Code**. **Next**.




# APP Configuration-Quick Settings

**Step 6:** Cloud Platform Address (e.g. **European Server**);  
COMM. Mode : **Wireless Connection Mode**;  
**Wi-Fi Name and password** of the network.

**Step 7:** Confirm that the device, router, and cloud platform communication is normal, select **Done**, and the network configuration is successful.



**Android users** can automatically obtain the corresponding wifi name  
**Apple users** need to manually input the WiFi name



## Download and Registration

1. **Download HYXipower APP.**
  2. **Register the account of the person in charge of the organization.**
- 

## Near-end Configuration

### **Register the WiFi microinverter to the cloud server through Configuration.**

All HYXiPOWER's equipment is managed by the cloud platform. After the equipment is registered to the cloud server, it can be managed uniformly through the cloud platform.

---

## Crear Plant for Users

### **Create a plant for users**

Manage the equipment through the Plant and check the equipment status, system power generation and usage, etc.

---

## Check Signal Strength

### **Check the signal strength of the microinverter after the configuration.**


Ensure that microinverter, software and mobile data transmission are normal.

---


# APP configuration - Create a Plant for the owner




**Step 1:** Disconnect the phone from the Microinverter's WiFi. Make sure your phone has Internet access



**Step 2:** Log in to your organization account, click the **Add Plant button**







**Step 3:** Scan the QR code of the Microinverter or add it through the Recently debugged device



# APP configuration - Create a Plant for the owner

**Step 4: Add owner - manually add or scan the owner's QR code to bind.** Manually add - enter the email address or mobile phone number of the Plant owner. If the owner is not registered, click to help him register and bind. The system will generate a random password and send a text message or email to the registered account





# APP configuration - Create a Plant for the owner



Step 5: Plant name-Plant type(**House hold Use**)-  
Region-Time Zone

**Add Plant**

Progress: 1, 2, 3, 4

\*Plant Name: recoderag@163.com20 24-04-10

\*Plant Type: **Household Use**

Region: 中国浙江省杭州市滨江区

Plant Address: 浙江省杭州市滨江区长河街道滨兴路1399号-大华股份(总部)

\*Time Zone: (UTC+08:00) Beijing, Chongqing, Hong Kong, Urumqi

More Info

Previous Next

**Plant Type**

Please select the correct power station type

**Household Use**  
For small and medium-sized projects, typically under 100 kW, dominated by microinverters, residential energy storage, and string systems

**Industry and Commerce**  
For large-scale commercial and industrial projects, typically under 100 kW, dominated by high-capacity household energy storage and high-capacity string systems

**Energy Storage**  
For projects dominated by commercial and industrial energy storage cabinets, typically over 100 kW

Previous Next

Step 6: **More Info-Next.**

**Add Plant**

Progress: 1, 2, 3, 4

\*Plant Name: recoderag@163.com20 24-04-10

\*Plant Type: **Household Use**

Region: 中国浙江省杭州市滨江区

Plant Address: 浙江省杭州市滨江区长河街道滨兴路1399号-大华股份(总部)

\*Time Zone: (UTC+08:00) Beijing, Chongqing, Hong Kong, Urumqi

More Info

Previous Next

**Add Plant**

Progress: 1, 2, 3, 4

Photovoltaic installed capacity: Please Enter kWp

Number of Strings: Please Enter

Grid Connection Type: **Feed All to Grid**

Contribution Type: **Full Payment by Owner**

Contact Phone No: Please Enter

Remarks: Please Enter

Plant Image: Upload


Show Less

Previous Next



# APP configuration - Create a Plant for the owner

**Step 6:** Fill in Electricity Price Type, Currency and Revenue per KWh, select Finish, and the Plant is successfully created.



## Download and Registration

1. **Download HYXipower APP.**
  2. **Register the account of the person in charge of the organization.**
- 

## Near-end Configuration

### **Register the WiFi microinverter to the cloud server through Configuration.**

All HYXiPOWER's equipment is managed by the cloud platform. After the equipment is registered to the cloud server, it can be managed uniformly through the cloud platform.

---

## Crear Plant for Users

### **Create a plant for users**

Manage the equipment through the Plant and check the equipment status, system power generation and usage, etc.

---

## Check Signal Strength

### **Check the signal strength of the microinverter after the configuration.**





Ensure that microinverter, software and mobile data transmission are normal.

---


# APP Configuration-Create Plant for Owner



## Step1: Plant- Device- Communication Device- Real-time Signal Strength.



# Installation Acceptance



**Step 1:** Select **Plant - User's Plant - Device**, and ensure that the online state of device is correct.

**Step 2:** After installation is completed, continuously monitor for more than half an hour, select **Statistics - Energy Analysis**, view the realtime power statistics curve, and ensure that the power station has started generating electricity normally.

**After confirming that all the above are normal, it indicates that the device installation and configuration is successful!**

# THANKS

Zhejiang Hyxi Technology Co., Ltd.

Quality

Innovation

Efficiency

Win-win

Dec. 2023