

HYXI DMU

HYX-DMU-4G

HYX-DMU-W



Convenient & User-Friendly

- Plug-and-play

Stable & Reliable

- Encrypted data transmission for security
- Local storage with resume capability, ensuring no data loss

Smart & Manageable

- 4G, Wi-Fi, and Ethernet communication capability
- On/off-site software updates, parameter configuration, and fault analysis

Product Model	HYX-DMU-W	HYX-DMU-4G
Communication to Microinverter		
Signal	Sub-1G	
Monitoring Data Limit From Solar Panels	400	
Communication to Hyxi Cloud		
Ethernet	RJ45x1, 100Mb/s	
Wireless	WiFi:802.11b/g/n	4G:TDD-LTE, FDD-LTE 3G:SCDMA 2G:GSM/GPRS
Data Acquisition Interval	5 min	
Power Supply (Adapter)		
Type	External adapter	
Adapter Input Voltage / Frequency	100 - 240V AC / 50 - 60Hz	
Adapter Output Voltage / Current	12V / 1A	
Power Consumption	1.5W	2.5W
General Data		
Operating Ambient Temperature	- 20 to +65°C	
Dimensions (W*H*D)	106*216*79mm (with base)	
Weight	320g	
Cooling	Natural Cooling	
Degree of Protection	IP20	
Installation Method	Desktop mounting / Wall mounting	