

# HIGH VOLTAGE BATTERY

## HYX-E50/100/ 150/200-H



### Safe & Reliable

- A+ grade cells with automotive-grade standard
- Smoke detection, active pressure relief
- IP65, C4 salt spray resistance

### Convenient & User-Friendly

- Flat design for easy integration
- Quick-plug interface for simple installation
- Stackable design for 5-20kWh capacity flexibility

### Efficient & Durable

- 35A fast charging/discharging support
- LiFePO4 cells with 6000+ charge/discharge cycles
- Optional PV module pre-heating for broad applications

### Smart & Manageable

- Automotive-grade BMS for efficient energy management
- Scenario-based app with real-time energy monitoring
- AI-powered cloud with 24/7 alerts and optimization

# HYX-E50/100/150/200-H

## Technical Specifications



Battery System	HYX-E50-H	HYX-E100-H	HYX-E150-H	HYX-E200-H
Total Battery Capacity	5.3kWh	10.6kWh	15.9kWh	21.2kWh
Usable Capacity <sup>1</sup>	4.5kWh	9.0kWh	13.5kWh	18.0kWh
Nominal Voltage	102.4V	204.8V	307.2V	409.6V
Working Voltage	86.4 - 115.2V	172.8 - 230.4V	259.2 - 345.6V	345.6 - 460.8V
Nominal Output Power	3.0kW	6.0kW	9.0kW	12.0kW
Cell Type	LiFePO4			
Max. Charging/Discharging Current	35A			
SOC Indicator	4*LED (25%, 50%, 75%, 100%)			
State Indicator	2*LED (work, alarm)			
Communication	CAN, RS485			
Working Temperature	-10 to +50°C (heating version -20 to +50°C)			
Ingress Protection Rating	IP65 (PACK IP67)			
Working Humidity	5 - 95% RH			
Working Altitude	< 4,000m			
Calendar Life	> 6,000 (70%EOL)			
Dimensions (W*H*D)	700*600*200mm	700*950*200mm	700*1,300*200mm	700*1,650*200mm
Net Weight	58.6kg	102.6kg	146.6kg	190.6kg
Alarms	Over charge / Over discharge / Over current / Over temperature / Short circuit			
Warranty	10 years			

<sup>1</sup>: Test conditions: 100% depth of discharge, 0.2C rate charge & discharge at 25°C, at the beginning of service life.