

# Three-Phase String Inverter Installation Guide

## HYX-H(5-12)K-HT

### -General

Delivery and Service Center

品质

创新

高效

共赢

V2.0 – 2025/06

# CONTENTS


**01** Program Overview

**02** Installation Preparation


**03** Device Installation

**04** App Configuration

# Program Overview-System Wiring Topology Diagram




# Program Overview-Hybrid Inverter Overview



No	Name	Description
1	LED indicator panel	Display the status of the inverter
2	Heat Sink	for ventilation and heat dissipation
3	Bracket	Fix the hybrid inverter
4	DC Switch	PV panel DC power input switch
5	DC switch locking hole	DC keyhole reserved
6	DC inputs	DC input from the panels to the inverter
7	Battery Input	the connection port between inverter and battery

No	Name	Description
8	DCS Terminal	Data communication stick connection port
9	Battery Terminal	Inverter and battery communication terminal, standard RJ45 port
10	Communication Hub	Meter RS485 communication/dry contact/DRM (Australia)/parallel communication/other communications
11	Off-grid load port	AC output port for off-grid loads
12	AC Terminal	for the inverter AC grid Connection

# Program Overview-BDU Introduction



Battery Disassembly Diagram

Battery System

No.	Explanation
1	Battery Distribution Unit (BDU)
2	Display Panel
3	Emergency Stop
4	High-voltage negative terminal
5	High-voltage positive terminal
6	Debug port
7	Inverter com port
8	High-voltage power button
9	12V low-voltage power button

**Note:** When starting the battery, short press the "POWER" low-voltage power button, then long press the "ON/OFF" high-voltage power button for about 5 seconds. When you hear a "click" sound from the relay, it means the battery has started;

# Program Overview- DCS Startup Check



## RESET button Operation Guide:

- 1、Double press to restart the device;
  - 2、Press four times to restore factory settings;
- Operation must be completed within 1 second;

No.	Light Indicators	Status	Explanation
3	POWER	Solid	DCS on
		Off	DCS off
4	NET	Solid	Connected to the cloud server
		Blink	Connecting to the cloud server
		Off	Connection failed
5	COM	Solid	Communicated with inverter
		Blink	Communicating with inverter
		Off	Communication failed

◆ Normal sign: After completing local debugging, three lights remain steadily lit.

# Program Overview-Meter Introduction



**The DTSU666 three-phase energy meter**

The DTSU666 three-phase energy meter is an advanced device integrating high-precision metering, remote communication, and intelligent management. Equipped with a high-performance metering chip, this meter ensures accurate power measurement and supports real-time energy monitoring, enabling users to track electricity consumption effectively. Additionally, the DTSU666 features an RS485 communication interface and wireless modules, facilitating remote data exchange and centralized monitoring, thereby significantly enhancing operational efficiency.



**Current Transformer**

The CT (Current Transformer), as a critical component of the DTSU666 energy meter, employs a non-contact measurement method, enhancing safety and reliability. It enables accurate high-current measurement and adapts to varying current and voltage levels, significantly expanding the meter's application scope.



# CONTENTS

**01** Program Overview

**02** Installation Preparation

**03** Device Installation

**04** App Configuration



## 2.1 Installation Preparation-Preparation List










The following product list is **NOT** included in the pre-sales configuration and **must be purchased separately**. Before system installation, ensure all devices and tools are fully prepared.

No.	Name	Explanation	Specifications
1	PV Cable	Cable for connecting photovoltaic panels to the inverter, compliant with outdoor multi-core copper cable standards (1000V, 18A).	4~10mm <sup>2</sup>
2	Communication Cable	485 communication cable for connecting the inverter and electricity meter.	RVVP two-core shielded cable, 0.5mm <sup>2</sup>
3	AC Output Cable	For AC-side wiring of the inverter, using a five-core outdoor copper cable.	4~10mm <sup>2</sup>
4	Backup Output Cable	For Backup-side wiring of the inverter, using a five-core outdoor copper cable.	4~10mm <sup>2</sup>
5	Ethernet Cable	For communication between the inverter and battery, a standard Ethernet cable is used. (Include one 2-meter-long Ethernet cable; if the length is insufficient, purchase separately.)	Standard
6	Ground Wire	For equipment grounding purposes.	4~10mm <sup>2</sup>
7	Battery Power Cable	Power cable for connecting the battery and inverter, must comply with 600V and 35A standards. (Optional battery power cable can be selected when placing future product orders.)	6mm <sup>2</sup>

## 2.2 Installation Preparation–Common Product List



The following product list is included in the pre-sales configuration.  
Before system installation, ensure that all devices and tools are fully prepared.

No.	Product	Picture	Explanation
1	Hybrid inverter		Include one inverter and related inverter accessories.
2	Battery		Include a Battery Distribution Unit (BDU) and battery modules for electrical energy storage.
3	Three-Phase Meter		Measure circuit voltage, current, power, etc.
4	Current Transformer		Used to measure the grid-side AC current, enabling the inverter to control power output and prevent backflow. Note: During installation, the arrow must point toward the grid.
5	DCS		After registering the device to the cloud server, it can be centrally managed via the cloud platform.
6	Ethernet Cable		The device comes with a 2-meter-long Ethernet cable. If the length is insufficient, you will need to procure one separately.
7	Wall-mounted bracket		Wall-mounted bracket for securing the inverter.

# 2.3 Installation Preparation–Tool Installation



## Installation Tool



Electric Drill



Heat Gun



Hex Key



Wire Stripper



Hydraulic Pliers



Crimping Tool



Screwdriver



Marker Pen



Utility Knife



Multimeter




Tape Measure



Hammer

## Protect Tool



Protective Mask



Safety Glasses



Insulated Safety Shoes



Insulating Gloves

# CONTENTS

**01** Program Overview

**02** Installation Preparation

**03** Device Installation

**04** App Configuration

# 3.1 Device Installation-Unpacking Inspection

## Inverter Unpacking Inspection:


- Check if the device hardware and ports are intact.
- Check if the device accessories are intact

No	Name
1	Hybrid Inverter
2	Bracket
3	Communication Connector
4	AC Connector
5	Backup Connector
6	Battery Terminal (female)
7	Battery Terminal (male)
8	Bracket Screw
9	RJ45 waterproof terminal
10	PV Insulation Terminals

1



2



3

4

5

6



10



9

8

7

## 3.2 Device Installation–Environment Requirements


1. Suitable for both indoor and outdoor installation.
2. -30°C to +60°C, 0~100% relative humidity (RH).
3. Select a shaded location to avoid direct sunlight and protect against rain/snow.
4. Ensure proper ventilation for heat dissipation.
5. The mounting structure must support at least 4 times the inverter's weight.
6. Mount vertically or tilted backward  $\leq 15^\circ$  to optimize thermal performance.
7. Do NOT install forward-facing, backward-facing, upside-down, horizontally, or sideways.
8. For multi-unit installations, maintain  $\geq 300\text{mm}$  clearance between inverters.





## 3.3 Device Installation-Physical Installation




Fix the mounting bracket and inverter as follows:



When installing multiple inverters, the distance between two inverters should be  $> 300\text{mm}$ .




Bracket Specification:



**Note:** Before installing the equipment, please ensure the photovoltaic panels have been installed and the cables have been laid in place;



## 3.4 Device Installation-Grounding Cable Connection



**Step 1:** Strip a certain length of the insulation layer of the power cable as shown in the figure, the length is  $L=E+(2-3)\text{mm}$  as shown in the figure.


**Step 2:** Pass the cable through the hot melt sleeve and insert it into the terminal.

**Step 3:** Use a crimping pliers to press the terminal and the cable tightly together.

**Step 4:** Adjust the hot melt sleeve to cover the end of the terminal and the power cable, and use a hot air gun to blow the hot melt sleeve to wrap the power cable and the end of the terminal.

**Step 5:** Use a screwdriver to fix the ground wire to the grounding position of the inverter.

## 3.5 Device Installation-DC Connectors



**Step 1:** Keep the switch on the inverter in the off state.

**Step 2:** Strip about 7 mm of insulation layer of all DC cables.


**Step 3:** Use crimping pliers to press the cold-pressed terminal to the cable.

Note that the terminals of the positive and negative poles are different, and the positive cold-pressed terminal is slightly longer than the negative cold-pressed terminal.

**Step 4:** Pass the cable through the cable gland, insert the insulating sleeve and tighten it, and gently pull the cable to ensure a tight connection. Tighten the gland and insulating sleeve with a force of 2.5~3N·m, and insert the assembled terminal interface into the photovoltaic connector until you hear a "click".

**Step 5:** Use a multimeter to check whether the polarity of the photovoltaic string connection cable is correct. Step 6: Connect the PV connector to the corresponding terminal on the inverter until you hear a "click".

## 3.6 Device Installation-AC Connector



**Step 1:** Use a T20 center-hole Phillips screwdriver to tighten the locking plate screws to a torque of  $1.2 \pm 0.1 \text{ N}\cdot\text{m}$ .

**Step 2:** Insert the stripped wires into the corresponding wiring holes according to the wire sequence.

**Step 3:** Use a T8 Phillips screwdriver to crimp the wires, with a torque of  $1.2 \pm 0.1 \text{ N}\cdot\text{m}$ .





**Step 4:** Insert the stripped wires into the locking wire nut and the main body in sequence (the soft wire needs to be riveted with an insulated terminal).

**Step 5:** Insert the cables into the rubber core according to the wire sequence, observe the cables in place through the perspective hole, and crimp the screws to a torque of  $4 \pm 0.1 \text{ N}\cdot\text{m}$ .

**Step 6:** Insert the main body into the rubber core and hear a "click" sound.


**Step 7:** Use an open-end wrench to tighten the nut (torque  $10.0 \pm 0.1 \text{ N}\cdot\text{m}$ ), and the installation is completed after a "click, click" sound.

## 3.7 Device Installation-Backup Connector 1


<div data-bbox="180 208 1161 285"><b>1</b> Prepare material</div> <div data-bbox="180 285 1161 782"><p>1-Seal gland 2-Seal 1 3-Seal 2 4-Cable housing 5-Plug 6-Cable</p><p>Notes: 1. Cable diameter: 11-19mm Mounting with sealing 1 &amp; 2 2. Cable diameter 19-26mm Mounting without sealing 1</p></div>	<div data-bbox="1161 208 2150 285"><b>2</b> Pass cable through gland, sealing and cable shell</div> <div data-bbox="1161 285 2150 782"></div>
<div data-bbox="180 782 1161 856"><b>3</b> Cable Stripping</div> <div data-bbox="180 856 1161 1349"><p>12.5 ±0.5 4.0 ±1</p></div>	<div data-bbox="1161 782 2150 856"><b>4</b> Insert the stripped wire into the corresponding pole. Tighten the screws when the wires are in place.</div> <div data-bbox="1161 856 2150 1349"><p>Mounting torque: 1.2 ~1.5 N.m</p></div>

## 3.7 Device Installation-Backup Connector 2

- 5** Install plug adapter, sealing parts, gland on cable shell.




- 6** Tighten the torque 7 ~ 7.5 N.m




46

### Disassembly instructions





## 3.8 Device Installation - Meter Installation



**Step 1:** Pull the crimping assembly out of the communication terminal;

**Step 2:** Insert the meter RS485 2pin wire into the communication terminal as follows, and then strip the wire;


**Step 3:** Clamp the stripped meter RS485 2pin wire onto the crimping element (press the yellow button), see Equipment Installation 9 for details;

**Step 4:** Insert the waterproof rubber plug into the unused hole;

**Step 5:** Remove the inverter COM port cover, insert the communication terminal, and lock the pull tab;

**Step 6:** Connect the meter to the grid in parallel, see Equipment Installation 10 for details;

**Step 7:** Pass the magnetic rings of the three current transformers through the circuit breaker to the three-phase live wires of the grid, and note that the arrows need to face the direction of the grid (as shown below).



## 3.9 Device Installation- Meter Connection



COM Communication Port  
(Close-up View)

### Note:

Pin 2 on the COM port connector corresponds to RS485 Communication A on the meter, and Pin 4 corresponds to RS485 Communication B. (It is recommended to use twisted-pair cable for connection.)



## 3.9 Device Installation-Meter Connection




U : Line Wire R  
V : Line Wire S  
W: Line Wire T  
N : Neutral Wire

**Wiring Diagram  
(Top Side of  
Electricity Meter)**

### Wiring Diagram (Top Side of Electricity Meter):

- Connect the three-phase live wires and neutral wire between the grid and the inverter as shown in the diagram. The phase sequence of the upper terminals L1, L2, L3 must correspond one-to-one with the lower CT terminals IA (13,14), IB (16,17), IC (19,21). Ensure all CT arrows point toward the grid side.




**Wiring Diagram  
(Bottom Side of  
Electricity Meter)**

### Wiring Diagram (Bottom Side of Electricity Meter):

- For the current transformer (CT) communication wires connected to the three-phase live lines: **the white wire corresponds to I\*, and the blue wire corresponds to I.**
- The inverter communicates with the meter via **PIN 2 (A) and PIN 4 (B)** of the COM port.

## 3.9 Device Installation-DCS Installation



### DCS communication stick installation (4G version)

**Step 1:** Remove the DCS protective cover and insert the SIM card;

**Step 2:** Install the DCS waterproof cover;

**Step 3:** Remove the waterproof cover at the inverter communication interface;

**Step 4:** Insert the DCS into the corresponding communication terminal at the bottom of the inverter and tighten it to ensure it is firm.

### DCS communication stick installation (Wifi version)

**Step 1:** Remove the waterproof cover at the inverter communication interface;

**Step 2:** Insert the DCS into the corresponding communication terminal at the bottom of the inverter and tighten it to ensure it is firm.

## 3.10 Device Installation-Battery Installation



**Step 1:** Place the battery base on a flat surface.

**Step 2:** Carefully place the battery module on the battery base, ensuring that the interface connection is accurate (the process needs to be careful and slow). If there are multiple battery modules, stack them one by one.




**Step 3:** Shake gently repeatedly to ensure that the installation is firm.

**Step 4:** Carefully assemble the battery management unit from the top, ensuring that the interface connection is accurate (the process needs to be careful and slow).

**Step 5:** Shake gently repeatedly to ensure that the installation is firm.

**Note:** When there are 3-5 battery modules stacked in the battery system, the stability of the equipment needs to be considered, and the installation bracket needs to be considered if necessary.

## 3.10 Device Installation-Battery Installation



**Step 1:** Put the three accessories (socket, sealing ring, nut) of the two sets of waterproof terminals on the standard network cable.

**Step 2:** Assemble the connector.

**Step 3:** Plug the two ends of the network cable into the corresponding network ports of the inverter and battery BDU respectively, and tighten the nuts.


**Step 4:** Use a crimping pliers to press and connect the battery power line and the connector. Pay attention to distinguish the positive and negative poles, orange is positive, and black is negative.

**Step 5:** Plug the battery power line terminal into the battery BDU until you hear a "click".

**Step 6:** Refer to the PV side connector production method to make the connector at the other end of the battery power line. After completion, insert it into the battery power input terminal of the inverter until you hear a "click".

## 3.11 Device Installation - Inverter Startup

1. Plug in the AC-side connector and turn on the circuit breaker. After closing, the meter will light up and the bulb will illuminate.
2. Turn on the DC switch on the inverter.
3. Connect the PV panel connectors on the DC side and insert the plug.
4. Verify the inverter's indicator light status. The light status shown below indicates normal operation.




- ◆ Normal sign: Three lights on, one light off.
- ◆ Note: Before starting the inverter in the training room, ensure the switch is in the ON position.

NO.	Indicator	Status	Explanation
1	POWER	Solid	Inverter Power on
		Off	Inverter Power off
2	GRID	Solid	Grid Side normal
		Average blinking	Grid Side abnormal
		Double blinking	Not connected with grid
3	COM	Solid	Communication normal
		Average blinking	Communication failure between inverter and meter
		Double blinking	Communication failure between inverter and battery
		Off	Inverter communication failure with both meter and battery
4	ALARM	Off	No alarm from inverter
		Average blinking	Alarm from inverter
		Double blinking	Other alarms

## 3.11 Device Installation - Inverter Startup

1. Plug in the AC-side connector and turn on the circuit breaker. After closing, the meter will light up and the bulb will illuminate.
2. Turn on the DC switch on the inverter.
3. Connect the PV panel connectors on the DC side and insert the plug.
4. Verify the inverter's indicator light status. The light status shown below indicates normal operation.



- ◆ Normal sign: Three lights on, one light off.
- ◆ Note: Before starting the inverter in the training room, ensure the switch is in the ON position.

NO.	Indicator	Status	Explanation
1	POWER	Solid	Inverter Power on
		Off	Inverter Power off
2	GRID	Solid	Grid Side normal
		Average blinking	Grid Side abnormal
		Double blinking	Not connected with grid
3	COM	Solid	Communication normal
		Average blinking	Communication failure between inverter and meter
		Double blinking	Communication failure between inverter and battery
		Off	Inverter communication failure with both meter and battery
4	ALARM	Off	No alarm from inverter
		Average blinking	Alarm from inverter
		Double blinking	Other alarms

# CONTENTS

**01** Program Overview

**02** Installation Preparation

**03** Device Installation


**04** App Configuration



## 4.1 APP Configuration-Registration




- 1、 Download HYXipowerAPP
- 2、 Register the account of the person in charge of the organization



**Register the DCS communication stick to the cloud server through local debugging.**

All Hyxipower equipment is managed using the cloud platform. After the equipment is registered to the cloud server, it can be managed uniformly through the cloud platform.



**Create a power station for users**

You can manage the equipment through the power station and check the equipment status, system power generation and usage, etc.

# 4.1 APP Configuration-Registration



The entire process requires 2 email accounts: Organization and Owner.

**Step 2:** Download the APP and **register**

## Method 1

Search "Hyxipower" in the Application Store

- APP store (IOS)
- Google play

## Method 2

Scan the QR code download the APP



**Step 3 :** According to the country or region, select **server**, select **organization** , fill in the relevant information and **register**.

Language

HYXiPOWER

hyxipower01@bccto.cc

Password

Forgot Password? **Register Now**

☒ I agree to the [Terms of Use](#) and I have read the [Privacy Policy](#)

Login

Device Installation Demo Site



Select Role

Please select the relevant server for your area

Select Your Server **European Server**

If Your Role Is An Installer Or A Distributor, Please Register For The Following Role.

**Register as Organization**  
Installer or Distributor

Register as Owner

**Register as Owner**  
Plant Owner

If You Have Only Installed A Balcony Photovoltaic System, Please Register The Following Roles.

**Registered Balcony System Homeowner**  
Balcony System Owner

Register as Organization

Note: If your organization or company has registered for an organization account in this system, you do not need to register again. Please contact your administrator to add you to the member list

Organization/ Company Name  Please Enter

Registration Method

Please Enter  @hotmail.com

Please Enter  **Send**

Complete Info


Password  Please Enter

Confirm Password  Please Enter

**Register**

☒ I agree to the [Terms of Use](#) and I have read the [Privacy Policy](#)



## 4.2 APP Configuration-Near-end Commissioning



## 4.2 APP Configuration-Near-end Commissioning

**Step1:**Click **Device Installation** in **Service** interface.

Then scan the QR code of the Data Communication Stick. If failed ,click the Manually Connect.



## 4.2 APP Configuration-Near-end Commissioning



**Step2:** Device login, initial password: hyxi0607. Log in and change the password, then save it.

If you forgot the password, quickly press the RESET button on the DCS four times to restore factory settings


The screenshot shows the 'Authentication' screen of the APP. At the top, there is a back arrow and the title 'Authentication'. Below this is a large, faint background image of a device. In the center, there is a small image of a black device. Below the device image, the text 'Current Device SN 60701233800024' is displayed. Further down, there is a dropdown menu labeled 'Installer' with a downward arrow, which is highlighted with a red box. Below the dropdown is a 'Password' field with a toggle icon. Underneath the password field is a link labeled 'Forgot Password' in green text. At the bottom, there is a green 'Log In' button, also highlighted with a red box.

## 4.2 APP Configuration-Near-end Commissioning

### Step3: Quick Settings

① **Device Management**: The DCS automatically reads the inverter's **SN and model number**.


**Meter settings**: 1. Grid type—**Three-phase**; 2. Configure meter—default address 1, install on **grid side**.





# 4.2 APP Configuration-Near-end Commissioning



**Step4:** ② **On-grid Settings:** Select the corresponding country's grid-code, then click Next.



**Step 5:** ③ **Device Settings** - Set feed-in power limit (enable and set to 0 to stop feeding grid).






## 4.2 APP Configuration-Near-end Commissioning

**Step6:** ④ **Communication Settings:** Wi-Fi Mode: Enter **Wi-Fi name and password**.

Wired Mode: Ensure automatic IP acquisition is enabled.

4G Mode: The APN, username and password will be recognized automatically, and proceed to next step after setup.



- Completion sign: Green checkmarks show between Device - Router - Cloud platform  
DCS shows three steady LED lights

## 4.3 APP Configuration-Create a Plant



Registration

1. Download HYXipower APP .
2. Register the account of the person in charge of the organization.



Near-end  
Commissioning

**Register the DCS communication stick to the cloud server through local debugging.**

All Hyxipower equipment is managed using the cloud platform. After the equipment is registered to the cloud server, it can be managed uniformly through the cloud platform.




Create a Plant

**Create a power station for users**


You can manage the equipment through the Plant and check the equipment status, system power generation and usage, etc.

## 4.3 APP Configuration-Create a Plant


**Step 1:** Disconnect the phone from the DCS' s WiFi. Make sure your phone has Internet access



**Step 2:** Log in to the organization account, click "Add Plant"




**Step 3:** Scan the QR code of the DCS or add it through Recently Debugged Device



## 4.3 APP Configuration-Create a Plant




**Step 4:** Add owner - manually add or scan the owner's QR code to bind. Manually add - enter the email address or mobile phone number of the Plant owner. If the owner is not registered, click to help him register and bind. The system will generate a random password and send a text message or email to the registered account



## 4.3 APP Configuration-Create a Plant

**Step 5:** Fill in basic information including Plant name, Plant type(**Household Use**), Region, Time Zone, and More information including Photovoltaic Installed Capacity, etc.



The image displays three sequential screenshots of the 'Add Plant' app interface, illustrating the configuration process for a plant.

**Screenshot 1: Add Plant (Step 3)**

The interface shows a progress bar with four steps: Add Device, Bind User, Basic Info, and Price Config. The 'Basic Info' step is currently active. The form includes the following fields:

- \*Plant Name: [Input field]
- \*Plant Type: Household Use >
- Region: 中国, 浙江省, 杭州市, 滨江区
- Detailed Address: 浙江省杭州市滨江区长河街道滨兴路1399号-大华股份(总部)
- \*Time Zone: (UTC+08:00) Beijing, Chongqing, Hong Kong S.A.R., Urumqi >
- Photovoltaic Installed Capacity: Please Enter kWp

Buttons: Previous, Next

**Screenshot 2: Plant Type**

Please select the correct plant type.

- ☒ **Household Use**  
Residential projects dominated by small-to-medium power microinverters, hybrid inverters, and string inverters.
- ☐ **Industry and Commerce**  
Commercial and industrial projects dominated by high-power string inverters.
- ☐ **Energy Storage**  
Projects dominated by commercial & industrial ESS.

**Screenshot 3: Add Plant (Step 4)**

The interface shows the progress bar with the 'Price Config' step now active. A note is displayed:


Note: Changes to electricity price types, currency units, prices, etc., will take effect immediately. However, the revenue calculation rules for the corresponding plants will take effect the next day. Unable to proceed with revenue estimation without configuring the electricity price.

The form includes the following fields:

- Electricity Price Type: Fixed Electricity Price >
- Currency: CNY >
- Revenue Per kWh: Please Enter

Buttons: Previous, Finish

## 4.3 APP Configuration-Create a Plant



**Step1:** Select the **plant**, enter the **user's plant interface**, go to the device interface, and ensure the devices are online and functioning normally.

**Step2:** After installation, continuously monitor for at least 30 minutes. Select **Statistics**, go to the Energy consumption analysis interface, check the real-time power generation curve to confirm the plant has started normal electricity production.

**After all the above checks are confirmed normal, it indicates successful installation and commissioning of the equipment!**



# THANKS

Delivery and Service Center

品质

创新

高效

共赢