

## Safety Data Sheets (SDSs)

Product Name: RECHARGEABLE LI-ION BATTERY

---

Commissioner: Zhejiang Hyxi Technology Co., Ltd.

---

**CVC Testing Technology Co., Ltd.**

# Safety Data Sheets (SDSs)

Ref, No.: RZUN012025-1296-DS1

Page 2 of 10 Pages

|                            |                                                                                                                                                                      |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name of Product            | RECHARGEABLE LI-ION BATTERY                                                                                                                                          |
| Type/Mode                  | HYX-E200-H 409.6V 52Ah 21.2kWh                                                                                                                                       |
| Commissioned by            | Zhejiang Hyxi Technology Co., Ltd.                                                                                                                                   |
| Commissioner address       | Room 216, Block A, Building 1, No. 57 Jiang'er Road, Changhe Street, Binjiang District, Hangzhou , Zhejiang Province                                                 |
| Supplier                   | Zhejiang LeapEnergy Technology Co. Ltd                                                                                                                               |
| Supplier address           | Room 220-116, Comprehensive Office Building, 222 Luyin Road, Qianjin Street, Qiantang District, Hangzhou City, Zhejiang Province, China                              |
| Inspection according to    | GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS, Rev.10)                                                                                |
| Emergency telephone number | +86-18958108657                                                                                                                                                      |
| Importer Information       | Name: HYXI TECHNOLOGY AUSTRALIA PTY LTD<br>Address: Level 1050 Clarence Street, SYDNEY NSW 2000<br>Tel: +61 (29) 0995-862<br>Email: AU.sales@hyxipower.com           |
|                            | Name: PING AN ELECTRIC POWER TECHNOLOGY PTY LTD<br>Address: 27 Glenvale Crescent, Mulgrave VIC 3170<br>Tel: 0395812098 / 0415613579<br>Email: finance@papower.com.au |
|                            | Name: Virtual Watt Pty Ltd<br>Address: 1E/528 Compton Road, Stretton, Queensland 4116<br>Tel: 1300 665 199<br>Email: admin@virtualwatt.com.au                        |
|                            | Name: ELSONS PTY LTD<br>Address: 37 BUSBY ST ALGESTER QLD 4115<br>Tel: 1300 019 628<br>Email: hello@elsons.com.au                                                    |
| Remarks                    | -                                                                                                                                                                    |
| Seal of CVC                |                                                                                                                                                                      |
| Date of issue: 2025-07-17  |                                                                                                                                                                      |

Approved by: Zhang Siyao

Reviewed by: Liu Zhen

Tested by: Lin Qingyuan

*Zhang siyao*

*liuzhen*

*Lin Qingyuan*

# Safety Data Sheets (SDSs)

Ref, No.: RZUN012025-1296-DS1

Page 3 of 10 Pages

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

### Product Identifier

Product name: RECHARGEABLE LI-ION BATTERY

Model: HYX-E200-H 409.6V 52Ah 21.2kWh

### Other means of identification

Synonyms: none

### Relevant identified use of Product and uses advised against

Recommended Use: Energy storage system

Uses advised against: -

### Details of the Supplier of the safety data sheet:

Name: Zhejiang LeapEnergy Technology Co. Ltd

Address: Room 220-116, Comprehensive Office Building, 222 Luyin Road, Qianjin Street, Qiantang District, Hangzhou City, Zhejiang Province, China

Telephone: +86-15157109062

E-mail address: wang\_mingbo@leapmotor.com

### Details of the Importer of the safety data sheet:

Name: HYXI TECHNOLOGY AUSTRALIA PTY LTD

Address: Level 1050 Clarence Street, SYDNEY NSW 2000

Telephone: +61 (29) 0995-862

E-mail address: AU.sales@hyxipower.com

Name: PING AN ELECTRIC POWER TECHNOLOGY PTY LTD

Address: 27 Glenvale Crescent, Mulgrave VIC 3170

Telephone: 0395812098 / 0415613579

E-mail address: finance@papower.com.au

Name: Virtual Watt Pty Ltd

Address: 1E/528 Compton Road, Stretton, Queensland 4116

Telephone: 1300 665 199

E-mail address: admin@virtualwatt.com.au

Name: ELSONS PTY LTD

Address: 37 BUSBY ST ALGESTER QLD 4115

Telephone: 1300 019 628

E-mail address: hello@elsons.com.au

### Emergency telephone number

Company Emergency Phone Number: +86-18958108657

Importer Emergency Telephone Call: See Importer Information

## SECTION 2: HAZARDS IDENTIFICATION

# Safety Data Sheets (SDSs)

Ref, No.: RZUN012025-1296-DS1

Page 4 of 10 Pages

## **Classification**

The watt-hour rate of the battery is 21.2kWh, it is belong to the lithium-ion battery class 9 dangerous goods.

The RECHARGEABLE LI-ION BATTERY(HYX-E200-H) consists of four Rechargeable Li-ion Battery(HYX-E50B-H) and one High Voltage Li-ion 50 Battery BDU , The Rechargeable Li-ion Battery(HYX-E50B-H) is tested according to Section 38.3 of the Manual of Tests and Criteria, the test report number is: RZUN2024-7361

## **Other information**

Caution! Avoid short circuit, place in high temperature environment, put into water, or damage the shell.

## **SECTION 3: Composition/information on ingredients**

### **Chemical characterization:** Mixtures

**Description:** Chemical power supply based on nonaqueous electrolyte. Composed by positive electrode, negative electrode, diaphragm, electrolyte and shell.

Hazardous ingredients:

| Common Chemical Name         | Chemical Formula                               | Concentration (%) | CAS No.    | EC No.    |
|------------------------------|------------------------------------------------|-------------------|------------|-----------|
| Lithium iron phosphate       | LiFePO <sub>4</sub>                            | 38.6%             | 15365-14-7 | 604-917-2 |
| Carbon black                 | C                                              | 0.95%             | 1333-86-4  | 215-609-9 |
| copper                       | Cu                                             | 6.4%              | 7440-50-8  | 231-159-6 |
| graphite                     | C                                              | 20.3%             | 7782-42-5  | 231-955-3 |
| aluminum                     | Al                                             | 4.0%              | 7429-90-5  | 231-072-3 |
| Vinyl carbonate              | C <sub>3</sub> H <sub>4</sub> O <sub>3</sub>   | 7.2%              | 96-49-1    | 202-510-0 |
| Methyl ethyl carbonate       | C <sub>4</sub> H <sub>8</sub> O <sub>3</sub>   | 10.8%             | 623-53-0   | 613-014-2 |
| Lithium hexafluorocarbon ate | LiPF <sub>6</sub>                              | 3.5%              | 21324-40-3 | 244-344-7 |
| polythene                    | (C <sub>2</sub> H <sub>4</sub> ) <sub>n</sub>  | 3.5%              | 9002-88-4  | 618-339-3 |
| Polyethylene terephthalate   | C <sub>10</sub> H <sub>12</sub> O <sub>6</sub> | 2.4%              | 25038-59-9 | /         |
| Carbonate allyl ester        | C <sub>4</sub> H <sub>6</sub> O <sub>3</sub>   | 1.5%              | 108-32-7   | 203-572-1 |
| Silicone rubber              | C <sub>2</sub> H <sub>6</sub> OSi              | 0.85%             | 63394-02-5 | 613-211-3 |

# Safety Data Sheets (SDSs)

Ref, No.: RZUN012025-1296-DS1

Page 5 of 10 Pages

## SECTION 4: First-aid measures

### **First aid measures:**

Eye Contact: Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact: Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation: Move to fresh air. If symptoms persist, call a physician.

Ingestion: Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Swallowing: Do not induce vomiting. Get medical attention.

### **Most Important Symptoms/Effects:**

No information available.

### **Indication of any immediate medical attention and special treatment needed:**

Inform physician. Treat symptomatically.

## SECTION 5: Fire-fighting measures

### **Suitable Extinguishing Media:**

CO<sub>2</sub>, dry chemical powder, wet sand, plenty of water (for cooling).

Unsuitable Extinguishing Media: No information available.

### **Protective Equipment and Precautions for Firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

HAZCHEM CODE: 4W.

### **Special hazards arising from the substance or mixture:**

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium batteries contain flammable ingredients that may vent, ignite and produce sparks when subjected to high temperature (>150°C), When damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

## SECTION 6: Accidental release measures

### **Personal precautions, protective equipment and emergency procedures:**

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

### **Environmental precautions:**

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

# Safety Data Sheets (SDSs)

Ref, No.: RZUN012025-1296-DS1

Page 6 of 10 Pages

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

## **Methods and material for containment and cleaning up:**

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non-combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

## **SECTION 7: Handling and storage**

### **Precautions for safe handling:**

Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Avoid mechanical or electrical abuse.

More than a momentary short circuit will generally reduce the battery service life. Avoid reversing battery polarity within the battery assembly. In case of a battery unintentionally be crushed, rubber gloves must be used to handle all battery components. Avoid contact with eyes, skin. Avoid inhalation. No smoking at working site. Materials to Avoid: Strong oxidizing agents, Corrosives.

### **Conditions for safe storage, including any incompatibilities:**

Store in a cool, well-ventilated area. Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short-circuits. Materials to Avoid: Strong oxidizing agents, Corrosives.

## **SECTION 8: Exposure controls/personal protection**

### **Engineering Controls:**

Use ventilation equipment if available. Safety shower and eye bath.

### **Personal Protective Equipment:**

Respiratory System: Not necessary under conditions of normal use.

Eyes: Not necessary under conditions of normal use.

Clothing: Wear appropriate protective clothing. ,

Hand: Safety gloves.

### **Other Protect:**

No smoking, drinking and eating at working site. Wash thoroughly after handling.

## **SECTION 9: Physical and chemical properties**

|          |                 |
|----------|-----------------|
| Physical | Form: Prismatic |
|----------|-----------------|

# Safety Data Sheets (SDSs)

Ref, No.: RZUN012025-1296-DS1

Page 7 of 10 Pages

|                                              |                                            |
|----------------------------------------------|--------------------------------------------|
| State                                        | Color: White                               |
|                                              | Odour: Odourless                           |
|                                              | Odor Threshold: No information available   |
| Change in condition:                         |                                            |
| pH, with indication of the concentration     | Not determined.                            |
| Melting point/freezing point                 | Not determined.                            |
| Initial boiling point and Boiling range:     | Not determined.                            |
| Flash Point                                  | Not determined.                            |
| Flammability (solid, gas)                    | Not determined.                            |
| Upper/lower flammability or explosive limits | Not determined.                            |
| Auto-ignition temperature                    | Product is not self-igniting.              |
| Decomposition temperature                    | Not determined.                            |
| Other Information                            | No further relevant information available. |

## SECTION 10: Stability and reactivity

**Reactivity:** Stable under recommended storage and handling conditions (see section 7).

**Chemical stability:** Stable under normal conditions of use, storage and transport.

**Thermal decomposition/conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of Hazardous Reactions:** None under normal processing.

**Hazardous Polymerization:** Hazardous polymerization does not occur.

**Conditions to avoid:** Strong heating, fire, Incompatible materials.

**Incompatible materials:** Strong oxidizing agents. Strong acids.

**Hazardous Decomposition Products:** Carbon oxides, other irritating and toxic gases.

## SECTION 11: Toxicological information

**Acute toxicity:** No data available.

**Skin corrosion/irritation:** No irritant effect.

**Serious eye damage/irritation:** Cause serious eye irritation.

**Respiratory or skin sensitization:** No sensitizing effects known.

**Specific target organ system toxicity:** No information available.

*Note: The internal battery materials may cause irritation to eyes and skin.*

## SECTION 12: Ecological information

# Safety Data Sheets (SDSs)

Ref, No.: RZUN012025-1296-DS1

Page 8 of 10 Pages

**Toxicity:** No further relevant information available.

**Persistence and degradability:** No further relevant information available.

**Bioaccumulative potential:** No further relevant information available.

**Mobility in soil:** No further relevant information available.

**Results of PBT and vPvB assessment:**

PBT: Not applicable.

vPvB: Not applicable.

**Other adverse effects:** No information available.

## SECTION 13: Disposal considerations

**Waste treatment methods:**

Recommendation: Lithium batteries are best disposed of as a non-hazardous waste when fully or mostly discharged. Contact a licensed professional waste disposal service to dispose of large quantities materials.

**Other disposal recommendations:**

Recommendation: Disposal must be made according to official regulations.

## SECTION 14: TRANSPORT INFORMATION

**EmS No:** F-A ,S-I

**Marine pollutant:** No

**Environmental hazards:** Not applicable.

**Special precautions for user:** Not applicable.

**Proper Shipping name:** Lithium ion batteries

**Hazard Class:** Class 9

**UN/ID Number:** UN3480

**Packaging Group:** II

**Road transport**

**Label for conveyance:** Class 9 lithium battery hazard label

The lithium ion batteries package complied with the Packing Instruction P903 of The Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)

## SECTION 15: Regulatory information

**International Regulation:**

GLOBALY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF  
CHEMICALS (GHS)



# Safety Data Sheets (SDSs)

Ref, No.: RZUN012025-1296-DS1

Page 9 of 10 Pages

Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations

IATA Dangerous Goods Regulations (DGR)

INTERNATIONAL MARITIME DANGEROUS GOODS CODE (IMDG CODE)

## **EU Regulation:**

Regulation (EU) 2020/878: Revised Requirements for EU Safety Data Sheets

EU regulation (EC) 1272/2008 on "Classification, Labeling and Packaging of Substances and Mixtures" (CLP)

Registration, Evaluation and Authorization of Chemicals (REACH)

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)

## **US Regulation:**

American National Standard for Hazardous Workplace Chemicals – Hazard Evaluation and Safety Data Sheet and Precautionary Labeling Preparation

US DOT, Code of Federal Regulations, Title 49, Transportation, PT. 100-185

## **AU Regulation:**

Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)

## **SECTION 16: OTHER INFORMATION**

This file is only effective to the batteries (HYX-E200-H) provided by commissioner Zhejiang Hyxi Technology Co., Ltd. The commissioner provides the composition information of batteries, and promises its integrity and accuracy. Users should read this file carefully, and use the batteries in correct method. CVC Testing Technology Co., Ltd. (CVC) doesn't assume responsibility for any damage or loss because of misuse of batteries.

---

## Important

1. The test report is invalid without the seal of CVC.
2. Nobody is allowed to photocopy or partly photocopy this test report without written permission of CVC.
3. The test report is invalid without the signatures of Ratifier, Reviewer and Testing engineer.
4. The test report is invalid if altered,
5. Objections to the test report must be submitted to CVC within 15 days,
6. This report is valid for the samples provided by commissioner only.

*The test data and test results given in this test report should only be used for purposes of scientific research, teaching and internal quality control when the CMA symbol is not presented.*

Address: No.3, Tiantai 1st Road, Kaitai Avenue, Science City, Guangzhou, Guangdong, China.

Tel: 020 32293888

FAX: 020 32293889

Post Code: 510663

E-mail: [office@cvc.org.cn](mailto:office@cvc.org.cn)

<http://www.cvc.org.cn>