



**BUREAU
VERITAS**

ATTESTATION of standard conformity

BV LCIE CHINA Number 2666AS01CJDJ60546
Product Microinverter
Reference HYX-M300-S, HYX-M400-S, HYX-M500-S
HYX-M300-SW, HYX-M400-SW, HYX-M500-SW
Issued to ZHEJIANG HYXI TECHNOLOGY CO., LTD
Address 9-10F, Building 3, Jiuyao Commercial Center, Zhunatang Street, Xihu District,
Hangzhou City, Zhejiang Province, P.R. China
Manufacturer ZHEJIANG HYXI TECHNOLOGY CO., LTD
Technical characteristics See below table

The submitted sample of the above equipment has been tested according to the following standards:

<i>Standards</i>	<i>Report number</i>	<i>Report date</i>
EN 50549-10:2022	CJDJ-ESH-P25120597	05/02/2026
EN 50549-1:2019 + A1:2023 for type A and type B plants		

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance

This verification does not imply assessment of the production of the product

Shanghai (P.R. China), Feb. 5th, 2026

Robin Wu
Senior Manager - PV, E&E China



This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document, are related to
the tested specimen of the described electrical sample.

Version: 13 / Feb.10, 2021



**BUREAU
VERITAS**

Characteristics of Microinverter			
Inverter model	HYX-M300-S	HYX-M400-S	HYX-M500-S
Input (PV DC)			
MPP voltage range [V]	16-60		
Max. input voltage [V]	65		
Max. input current per MPP tracker [A]	16		
AC connection			
Nominal AC voltage [V]	L/N/PE, 220 / 230 / 240 Va.c., 50/60 Hz		
Nominal output current [A]	1,3	1,74	2,17
Max. output current [A]	1,3	1,74	2,17
Nominal output power inverter [W]	300	400	500
Nominal apparent output power inverter [VA]	300	400	500

Characteristics of Microinverter			
Inverter model	HYX-M300-SW	HYX-M400-SW	HYX-M500-SW
Input (PV DC)			
MPP voltage range [V]	16-60		
Max. input voltage [V]	65		
Max. input current per MPP tracker [A]	16		
AC connection			
Nominal AC voltage [V]	L/N/PE, 220 / 230 / 240 Va.c., 50/60 Hz		
Nominal output current [A]	1,3	1,74	2,17
Max. output current [A]	1,3	1,74	2,17
Nominal output power inverter [W]	300	400	500
Nominal apparent output power inverter [VA]	300	400	500