

## AC-Coupled Micro Storage System

### HYX-MS3000AC/HYX-MS3000B

**Version 1.4-2603**  
Design and specifications are subject to change without notice



#### Advanced Performance

- 3014Wh large capacity, long battery life with 10000 cycles, 10 years warranty, 15 years design-life
- Support battery self-heating, usable at -20°C severe cold environment
- 3000W bidirectional inverter
- Max. 3000W off-grid power, portable use supported



#### Intelligent Design

- Plug and play, 2-minutes installation
- AI-powered cloud, automatically plan excess energy to maximize benefits according to the grid electricity prices
- All-in-one design, no need for an additional microinverter and offering all-in-one convenience and ease of use
- RGB intelligent lighting supported



#### Assured Safety

- Three levels of safety protection: early detection of risks, immediate warnings, and automatic triggering of protection mechanisms
- A+ grade cells with automotive-grade standard
- Safety at your hand with Ip66



#### Flexible Adaptability

- Flexible stacking expansion, no external wiring required, up to 18.086kWh
- Wide application range: small residential, balcony, garden, outdoor
- Zero energy waste with shelly smart meter and our own smart meter
- Compatible with any existing solar system, no rewiring, no upgrades

## Technical Specifications

### HYX-MS3000AC

Product Model	HYX-MS3000AC
<b>AC Output (on-grid terminal)</b>	
Rated AC Output Power	800W (Default)/1500(*Premium)
Max. AC Output Apparent Power	1500VA (Without Battery Pack) 3000VA (With Battery Pack)
Rated AC Output Voltage/Range	220 or 230 or 240 / 183 - 276V
Nominal AC Frequency/Range	50/45-55 or 60/55-65 Hz
Rated AC Output Current	3.64/3.48/3.34A (Default) 6.82/6.53/6.25A (*Premium)
Max. AC Output Current	6.82/6.53/6.25A (Without Battery Pack) 13.64/13.05/12.50A (With Battery Pack)
Power Factor Range	>0.99 (Default)/0.8 Leading-0.8 Lagging (Adjustable)
THDi (Rated Power)	<3%
<b>AC Input (on-grid terminal)</b>	
Max. AC Input Apparent Power	1500VA (Without Battery Pack) 3000VA (With Battery Pack)
Rated AC Input Voltage/Range	220 or 230 or 240 / 183 - 276V
Nominal AC Frequency/Range	50/45-55 or 60/55-65Hz
Max. AC Input Current	6.82/6.53/6.25A (Without Battery Pack) 13.64/13.05/12.50A (With Battery Pack)
Power Factor Range	>0.99 (Default)/0.8 Leading-0.8 Lagging (Adjustable)
THDi (Rated Power)	< 3%

## Technical Specifications

### HYX-MS3000AC

Product Model	HYX-MS3000AC
<b>AC Output (off-grid terminal)</b>	
Max. AC Output Apparent Power	1500VA (Without Battery Pack) 3000VA (With Battery Pack)
Max. AC Output Current	6.82/6.53/6.25A (Without Battery Pack) 13.64/13.05/12.50A (With Battery Pack)
AC Nominal Output Voltage/Frequency	220 / 230 / 240V, 50/60Hz
THDu (Linear Load)	<3%
<b>Battery Data</b>	
Battery Chemistry	LiFePO4
Battery Nominal Voltage	9.6V
Battery Nominal Energy	3014Wh
Max. Charging Power	1500VA (Without Battery Pack) 3000VA (With Battery Pack)
Max. Discharging Power	1500VA (Without Battery Pack) 3000VA (With Battery Pack)
Battery Cycle Life	≥10000 (@25°C±2°C, 60%EOL)*
<b>Other Technical Specification</b>	
Display	LED & APP
Ingress Protection Rating	IP66
Operating Ambient Temperature Range	-20 to +55°C*
Humidity	5% ~ 95% (No Condensing)
Altitude	3000m
Dimensions (W*D*H)	460*281*279mm
Weight	28kg
Cooling Concept	Natural Cooling
Communication	WiFi & Bluetooth
<b>Standard</b>	
Safety	IEC62109-1/-2
EMC	IEC62619, UN38.3, IEC/EN 61000-6-1, IEC/EN 61000-6-2, IEC/EN 61000-6-3, IEC/EN 61000-6-4
Grid Connection Standard	VDE4105, IEC61727/62116, CEI 0 21, EN50549-1, G98, G99, C10-11, UNE217002

\*Premium: Enabling this function must comply with local regulations and should only be performed by authorized personnel!

\*Support -20°C startup and automatically self-heat the device for a certain time to the charge temperature range.

Product Model	HYX-MS3000B
<b>Battery Data</b>	
Battery Chemistry	LiFePO4
Battery Nominal Voltage	9.6V
Battery Nominal Energy	3014Wh
Max. Charging/Discharging Power	1500/1500W
Battery Operating Voltage	6~10.95V
Battery Cycle Life	≥10000
Parallel Capability (pcs)	5
<b>Other Technical Specification</b>	
Communication Interface	CAN
Dimension (W*D*H)	460*274*296.5mm
Weight	26kg
Operating Temperature Range	-20 to +55°C
Max. Operating Altitude	3000m
Relative Humidity	5% ~ 95% (No Condensing)
Certification	UN38.3, IEC62619, CE
Installation Style	Floor-Mounted
Warranty	10years